

LABEL INFORMATION

SFP+ to SFP+
Direct Attach Cable xM
10G Copper Passive
S/N: YYMMDDSLxxxx

Describe(xM=Cable length)(Font: Arial)
Fixed Describe(Font: Arial)
CODE 128,CONTENTS:
YYMMDDSLxxxx

SN:YYMMDDSLxxxx

Serial number


YYMMDD
YY: 19 (2019), 20 (2020), 21 (2021).....
MM: (Month)
DD: (Date)

WIRING DIAGRAM

HIGH SPEED SIGNAL			
P1 SFP+		P2 SFP+	
PAD	SIGNAL	PAD	SIGNAL
19	TX-	12	RX-
18	TX+	13	RX+
12	RX-	19	TX-
13	RX+	18	TX+
GND GROUP	GND	GND GROUP	GND
GND Group: 01,02,06,08,10, 11,14,17,20		GND Group: 01,02,06,08,10, 11,14,17,20	
CONNECTOR SHELL		CONNECTOR SHELL	

*DC BLOCKING CAPS ON P1,P2 RX END.

LOW SPEED SIGNAL & POWER	
P1~P2(SFP+)	
PAD	SIGNAL
03	TX_Disable
04	SDA
05	SCL
07	RS0
09	RS1
15	VCCR
16	VCCT



SFP28 + SFP28 X L CM xxA

SFP28 ———— 26: 26 AWG
SFP28 ———— 28: 28 AWG
 30: 30 AWG
 L: Cable Length

Dwg. No.	S2220191203-01	Part No.	SFP28+SFP28XLCMxxA		
Projection		Title:	SFP28 to SFP28 Cable Assembly		
Unit mm	Scale 1:1	Drawn By	Jerry 06/12'20	679	Date rate 25G
				SHEET	1/1 Ver. No. X2

Materials:
Back/TOP Shells: Nickel Plated Zinc Alloy.
PCB: FR-4.
Pull Latch: Nylon.(Color: Deep Blue)
Rivets: Aluminum Alloy.
Cable: Twinax Cable.
IMPEDANCE:
Cable: 100±5 Ohms Differential.
Connector: 100±10 Ohms Differential.
**This Product Used IEEE802.3bj
Standard EEPROM Data
*RoHS Compliant**

OUPIN ENTERPRISE CO. LTD.